



OMEGA^{ONE}

professional equipment

<http://www.omegaone.gr> email: info@omegaone.gr

Tel: 0030 2103472270 Fax: 0030 2103476037



Potato Peeler PI-10

10 KG. / 22 POUNDS LOAD PER CYCLE.

**Stainless steel construction commercial potato peeler.
Also suitable to peel carrots and other similar products.**

- Construction in stainless steel.
- Lateral stirrers covered with silicon carbide abrasive (approved by NSF).
- Aluminium base plate lined with silicon carbide abrasive (approved by NSF), easily removable for cleaning purposes.
- Auto-drag of waste to the drain.
- Energy efficiency owing to engine optimisation.
- Lifting transparent polycarbonate cover, complete with locking and safety device.
- Aluminium door with hermetic seal and safety device.
- Waterproof control board (IP65): Improved reliability against moisture and water splash.
- Water inlet system with non-return air break.
- Auxiliary contact for external electric valve.
- 0-6min timer and possibility of continuous operation.

TECHNICAL SPECIFICATIONS

Hourly production: 200 Kg / 240 Kg
Capacity per load: 10 Kg
Timer (min-max): 0' - 6'
Single Phase: 550 W
Three phase: 370 W

External dimensions (WxDxH)
433 mm x 635 mm x 625 mm <m>

External dimensions with stand
433 mm x 638 mm x 1040 mm <m>

Net weight: 36 Kg

Noise level (1m.): 70 dB(A)
Background noise: 32 dB(A)

DEFAULT EQUIPMENT

- OPTIONAL EQUIPMENT
- Stainless steel floor stand.
 - Filter with no-foam feature.