

Category

Description

Code

Water coolers

Pressure water cooler

FK33



Optional
Water Filter



Filter Head VB-2

- Built-in valve allows cartridge change outs without shutting off the incoming water supply.
- 1/4" quick connect connections are compatible with plastic tubing



Cartridge AP2-C405SG

- Removes Chlorine, Bad taste and Odour, Benzene Toxaphene and Dichlorobenzene and Reduces Sediment, Cysts and Lead
- Filtration level below 0.5 Micron.

Technical features

- External casing in painted steel
- Stainless steel fountain top tested splash resistant equipped with mechanical pushbutton control jet and glass filler
- Refrigerant HFC – 134a
- Cooling unit made from stainless steel both the tank and the refrigerant tube
- Fan cooled condenser copper tube with aluminum fins

Technical Specifications

Cold water production (Lt/h)	33
Compressor power (HP)	1/4
Dimensions (wxdxh ø mm)	320 x 320 x 1000
Weight(Kgr)	26
Refrigerant (gr) R-134a cfc-free	180
Water outlet temperature (°C)	8-12
Power (W)	290
Voltage (V/Hz)	220-240/50

WATER INLET TEMPERATURE 20°C- ROOM TEMPERATURE 25°C

Installation guides

Water inlet	Drain	Electric cable
1/2" Bsp male thread	Flexible tube 3/4"	1.2m shuko plug

