



Specifications

Digital electronic thermostat.
 Externaal right-side condensing unit.
 Fan assisted evaporator foamed in the bacwall.
 Automatic evaporation of water condensation (model with motor).
 Defrosting by compressor stop (version with motor).
 Aytomatic heating system of compressor, depending on enviromment Temperature, to avoid freezing (version with motor).
 Bult with panels entirely made in inox.
 Internal glossy finishing, external schotch-brite.
 CFC and HCFC free high densiy polyurethane foam with 60mm thickness.
 Plain door made of inox AISI 304 18/10, magnetic seal on 4 sidew.
 Wickets made of inox AISI 304 18/10, insulated, provited with hinges, seals on 4 sides.
 Inox floor CSN
 Doors and witkets are suitable to be locked (on request).
 Holder device for containers .
 Removable waste funnels.
 Provided with bottom (on request).



MODELLO	RW1RD		RW2RD		RW3RD	
Εξωτερικές διαστάσεις External dimensions	1100x875x1210	(MxΠxY) mm (LxDxH) mm	1750x875x1210	(MxΠxY) mm (LxDxH) mm	2400x875x1210	(MxΠxY) mm (LxDxH) mm
Εσωτερικές διαστάσεις Internal dimensions	650x660x1080	(MxΠxY) mm (LxDxH) mm	1300x660x1080	(MxΠxY) mm (LxDxH) mm	1950x660x1080	(MxΠxY) mm (LxDxH) mm
Χωρ/τητα σε δοχεία. Capacity containers.	1	120 or 240ltr.	2	120 or 240ltr.	3	120 or 240ltr.
Θερμοκρασία: Temperature:	+2/+12	°C	+2/+12	°C	+2/+12	°C
Οικολογικό Freon: Ecological Freon:	R404A		R404A		R404A	
Ψυκτική ικανότητα: Refrigerant capacity:	335 *	W	362 *	W	467 *	W
Τάση (V / Hz): Voltage (V / Hz):	230/1/50		230/1/50		230/1/50	
Απορροφούμενη ισχύς: Absorbed potency:	420	W	451	W	515	W
Μικτό βάρος: Gross weight:	120	kg	167	kg	198	kg
VOLUME IMBALLO (m ³)	1,8		2,8		3,7	

* Temp. rif.: EVAP. -10° C; COND. +55° C

